

Purchase Order ROLLER/SOLAR SHADES

Page _____ of _____

Account #: _____ Company Name: _____

Contact: _____ Purchase Order #: _____

Ship To Address: _____

Phone: _____ Sidemark: _____

City: _____ State: _____ Zip: _____

Fax: _____ Date Required: _____

EMAIL: _____

Ship Via (circle one): FedEX Common Carrier Local Truck Will Call

Line	Sidemark	Qty	Mount ¹	Width	Length	Fabric Type ²	Fabric Color ³	*Image Printing Yes/No	Lift Type ⁴	Spring Assist ⁵	Lift Side ⁶	Control Length ⁷	Fabric Roll ⁸	Hembar Type ⁹	Fascia ¹⁰	Channels ¹¹		
																Side	Sill	Color
1																		
2																		
3																		
4																		
5																		
6																		
7																		
8																		
9																		
10																		

* Please complete and submit Image Printing Purchase Order Form

Purchase Order Footnotes:

1. Mount: (IM) - Inside Mount (OM) - Outside Mount
2. Fabric Type: Specify the type of material.
3. Fabric Color: Specify the color # and name.
4. Lift Type: (CHN-PL) - Chain Operated Clutch with Plastic Chain (CHN-SS) - Chain Operated Clutch with Stainless Steel Chain (CHN-WSS) - Chain Operated Clutch w/ WHT SS Chain (CHN-BSS)-Chain Operated Clutch w/BLK SS Chain (SPR) - Spring Operated (CHN-PLT-WMT) - Chain Operated Platinum Clutch w/SS Chain Wall Mount Bracket (CHN-PLT-CMT) - Chain Operated Platinum Clutch w/SS Chain Ceiling Mount Bracket (CHN-RLS) - Chain Operated R8/R16/R24 Clutch (MTR-BAT-RTS) - Somfy LT30 RTS Battery Powered Motor (MTR-DC-RTS) - Somfy ST30 RTS DC Powered Motor (MTR-AC-RTS) - Somfy ST50 or LT50 RTS AC Powered Motor (MTR-AC-HW) - Standard Hardwired 4-Wire AC Powered Motor (MRT-ILT) - Somfy ILT Intelligent Motor

5. Spring Assist: Please see Manual Clutch & Tube Matrix for Spring Assist Requirements.
6. Lift Side: (L) - Left Side Lift (R) - Right Side Lift
7. Control Length: If desired, the control length may be specified. Standard Chain Length = 75% of the Shade Drop Minimum Chain Length = 67% of the Shade Drop Standard AC Motor Cable Length = 6 Ft. / May be ordered up to 24 Ft. for an additional charge

8. Fabric Roll: (R) - Regular Roll (Standard - Fabric rolls off the back of the roller tube - Closest to the Glass) (V) - Reverse Roll (Optional - Fabric rolls off the front of the roller tube - Away from the Glass)
9. Hembar Type: (PKT) - Pocket Hembar (3-Side Welded) (EXT) - External Hembar (Alabaster, Anodized, Black, Bronze, White) (WH) - Wrapped Hembar (Fabric covered front, exposed aluminum on back)
10. Fascia: (3"SQR) - 3" Square Fascia (ALB, AND, BLK, BRZ, WHT) (4"SQR) - 4" Square Fascia (ALB, AND, BLK, BRZ, WHT) (3"RND) - 3" Round Fascia (AND, BLK, WHT) (4"RND) - 4" Round Fascia (AND, BLK, WHT) (3"FAB) - 3" Fabric Wrapped Fascia (AND, BLK, WHT) (4"FAB) - 4" Fabric Wrapped Fascia (AND, BLK, WHT) (PKT-NO-LIP) - Shade Pocket without Lip (AND, WHT) (PKT-LIP) - Shade Pocket with Lip (AND, WHT) (HNGR) - Mount Hanger with Closure Plate (AND, BLK, CASSR) - Cassette Residential w/fabric insert (ANO, ALAB, BRZ, WHT) (INS) - Inserted Fabric Valance
11. Channels: Specify side and/or sill channels if desired. (Alabaster, Anodized, Black, Bronze, White)

Motor Control Options:

If RTS motors are selected, specify the required controls.	
Radio Frequency (RTS) Controls:	Quantity
1 Ch. - RTS Hand Held Transmitter	
5 Ch. - RTS Hand Held Transmitter	
20 Ch. - RTS Hand Held Transmitter	
1 Ch. - RTS Wireless Wall Switch	
5 Ch. - RTS Wireless Wall Switch	
RS E-TRIM-1CH Transmitter Econoline	
RS E-TRIM -6CH Transmitter Econoline	
RS E-TRM-16CH Transmitter Econoline	
RTS 24 - Hour Timer	
RTS Sun Sensor	
16 Ch. - RTS Interface for Automation Integration	
If Standard 4-wire motors are selected, specify the required controls.	
Standard Controls:	Quantity
SPDT Paddle Wall Switch	
DPDT Pall Wall Switch	
GCS II 4-Motor Controller	
IGC Single Motor Controller	
IGC3N1 3 Motor Controller	
IGC Standard Wall Switch	

ALL MEASUREMENTS ARE BRACKET-TO-BRACKET

PLEASE SPECIFY FULL FABRIC NAME/PERCENTAGE/COLOR NAME & COLOR NUMBER