

Fabric Specifications: SheerWeave Performance + 2390/2410

Fire Classification: California U.S. Title 19 (small scale), ASTM E 84 (Class 1), NFPA 7012004 TM#1 (small scale), NFPA 101 (Class A Rating), UBC (Class I), BS 5867 2008 Part 2 Type B Performance, NFPA 701 TM#2 Large Scale and CAN/ULCS109 (large and small scale)

Bacteria and Fungal Resistance: ASTM E 2180, ASTM G22, AATCC30 Part 3, ASTM G21, ASTM D 3273, GREENGUARD Mold and Bacteria Standard ASTM 6329; includes Microban antimicrobial additives

Environmental Certification: GREENGUARD Certified and GREENGUARD for Children and Schools Certified

Lead Free: RoHS/Directive 2002/95/EC, US Consumer Product Safety Commission Section 101, ANSI/WCMA A100.12007 for lead content and REACH (EC 1907/2006) compliant

Standard Uses: Rollup shades, Roman shades, vertical blinds, panel tracks and screens

TrackLess: Technology minimizes the fiberglass yarns inherent tendencies to track when being rolled up in a shade. With TrackLess Technology these same fabrics now track less, roll up straighter and reduce shade fabrication time.

Handling and Cleaning Instructions: The metalized coating is fragile and must be handled with care to avoid damage. Do not scrub. Do not use tape, solvents or abrasive cleaners which could damage the fabric coating. Clean with a damp soft cloth using a mild detergent. Rinse with clean water and allow blind to dry in the down position. Do not slide metalized side across surfaces or into the cardboard tube without protective plastic wrapping. Do not use Radio Frequency sealing equipment on metalized fabric. Use only heat bars or ultrasonic sealing equipment for welding.



STYLE 2390

Standard Colors: Oyster, Oyster/Beige, Oyster/Pearl Gray, Beige, Beige/Pearl Gray, Pearl Gray, Charcoal, Charcoal/Gray, Charcoal/Chestnut, Charcoal/Alpaca

Standard Width: 63" and 96" (160.0 cm and 243.8 cm)

Standard Roll Length: 30 Linear Yards (27.4m)

Composition: 34% Fiberglass, 64% Vinyl on Fiberglass and 2% Aluminum Coating

Mesh Weight: 11.8 oz/yd² (379 g/m²)

Fabric Thickness: .018 in (0.46mm)

Openness Factor: Approximately 5%

STYLE 2410

Standard Colors: Oyster, Oyster/Beige, Oyster/Pearl Gray, Beige, Beige/Pearl Gray, Pearl Gray, Charcoal, Charcoal/Gray, Charcoal/Chestnut, Charcoal/Alpaca

Standard Width: 63" and 96" (160.0 cm and 243.8 cm)

Standard Roll Length: 30 Linear Yards (27.4m)

Composition: 34% Fiberglass, 64% Vinyl on Fiberglass and 2% Aluminum Coating

Mesh Weight: 14.1 oz/yd² (478 g/m²)

Fabric Thickness: .019 in (0.48mm)

Openness Factor: Approximately 3%

Light Transmittance: Includes light that comes through the openings and light that is reflected inward off the yarn.

Light Reflection: Represents light that is returned to the outside by the fabric.

Solar Transmittance: The total solar energy that passes through the fabric.

Solar Reflection Out: Represents the percent of all wave lengths of electromagnetic energy that are reflected out.

g-Value/SHGC: European equivalent for Solar Heat Gain Coefficient (SHGC). A rating that expresses the percentage of incident solar heat transmitted through a fenestration system. The solar heat gain coefficient is replacing the shading coefficient as the standard indicator of a window's shading ability. The lower the solar heat gain coefficient number, the less solar heat it transmits and the greater its shading ability.

UV Transmittance: Percent of Ultra Violet light transmitted through the fabric.

Color Rendering Index: A measurement of the fabrics effect on color on a scale of 1 to 100 where 100 represents no color distortion.

U-Value in W/m²K: Represents heat transmission in watts per square meter. This value does not represent US UValues.

SC (Shading Coefficient): Percentage of solar heat gain transmitted to the interior through the glass and shading system.

1 European standard EN 410: 1998 (E), Glass in building Determination of luminous and solar characteristics of glazing, European Committee for Standardization, April 1998.

2 European standard EN 12898:2001 (E), Glass in building

Determination of the emissivity, European Committee for Standardization, January 2001.

3 ISO 15099:2003 (E), Thermal performance of windows, doors and shading devices Detailed calculations.

4 European standard EN 673:1997 (E), Glass in building Determination of thermal transmittance (Uvalue) - Calculation method, European Committee for Standardization, October, 1997.

**SOLAR HEAT CONTROL PROPERTIES SHEERWEAVE STYLE
2390 PERFORMANCE+ FABRIC**

	Solar Trans	Solar Ref Out	Light Trans	Light Ref	% Open	UV Trans	Color Rend Index
P12 Oyster	8	71	8	70	5	7	99
P13 Oyster/Beige	8	72	8	71	5	6	99
P14 Oyster/Pearl Gray	7	71	7	70	5	6	100
Q20 Beige	8	72	8	71	5	7	98
Q21 Beige/Pearl Gray	7	71	7	70	5	6	99
V20 Pearl Gray	7	74	7	73	5	6	99
V21 Charcoal	8	71	8	70	5	7	100
V22 Charcoal/Gray	8	71	8	70	5	7	100
V24 Charcoal/Chestnut	8	71	8	70	5	7	100
V32 Charcoal/Alpaca	8	74	8	73	5	7	100

**SOLAR HEAT CONTROL PROPERTIES SHEERWEAVE STYLE
2410 PERFORMANCE+ FABRIC**

	Solar Trans	Solar Ref Out	Light Trans	Light Ref	% Open	UV Trans	Color Rend Index
P12 Oyster	5	73	5	72	3	3	99
P13 Oyster/Beige	5	73	5	72	3	4	99
P14 Oyster/Pearl Gray	4	73	4	72	3	4	99
Q20 Beige	5	73	5	72	3	4	98
Q21 Beige/Pearl Gray	5	72	5	71	3	4	99
V20 Pearl Gray	4	75	4	74	3	4	99
V21 Charcoal	4	71	4	70	3	4	100
V22 Charcoal/Gray	4	72	4	71	3	4	100
V24 Charcoal/Chestnut	4	72	4	71	3	4	100
V32 Charcoal/Alpaca	4	75	4	74	3	4	99

**SOLAR HEAT CONTROL PROPERTIES
SHEERWEAVE STYLE 2390 PERFORMANCE +**

	High Performance Glass				Low E Glass				6mm Double Clear Glass			
	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K
Glazing Performance	69	39	45	1.1	74	70	80	1.4	79	74	85	2.8
P12 Oyster	6	15	18	0.8	7	30	35	1.0	7	24	28	2.5
P13 Oyster/Beige	6	15	17	0.8	6	30	34	1.0	7	24	28	1.6
P14 Oyster/Pearl Gray	5	15	18	0.8	6	30	35	1.0	6	25	29	1.6
Q20 Beige	6	15	18	0.8	6	30	35	1.0	7	25	29	1.6
Q21 Beige/Pearl Gray	5	15	18	0.8	6	30	35	1.0	6	25	29	1.6
V20 Pearl Gray	5	15	17	0.8	5	29	33	0.9	6	24	27	1.5
V21 Charcoal	6	16	18	0.8	6	31	35	1.0	7	25	29	1.6
V22 Charcoal/Gray	6	16	18	0.8	6	30	35	1.0	7	25	29	1.6
V24 Charcoal/Chestnut	6	16	18	0.8	6	30	35	1.0	7	25	29	1.6
V32 Charcoal/Alpaca	6	15	17	0.8	6	24	28	1.0	7	24	28	1.6
	6mm Single Bronze Glass				6mm Single Clear Glass				3mm Single Clear Glass			
	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K
Glazing Performance	49	58	67	5.7	88	84	96	5.7	90	87	100	5.8
P12 Oyster	4	20	23	2.5	8	22	26	2.5	8	22	26	2.5
P13 Oyster/Beige	4	19	22	2.4	7	22	25	2.4	7	22	25	2.5
P14 Oyster/Pearl Gray	3	20	23	2.5	7	22	26	2.5	7	22	26	2.5
Q20 Beige	4	20	23	2.5	7	22	25	2.5	7	22	25	2.5
Q21 Beige/Pearl Gray	4	20	23	2.6	7	22	26	2.6	7	22	25	2.6
V20 Pearl Gray	3	19	22	2.4	6	21	24	2.4	6	21	24	2.4
V21 Charcoal	4	20	23	2.5	7	23	26	2.5	7	23	26	2.5
V22 Charcoal/Gray	4	20	23	2.4	7	23	26	2.4	7	22	26	2.5
V24 Charcoal/Chestnut	4	20	23	2.5	7	23	26	2.5	8	23	26	2.5
V32 Charcoal/Alpaca	4	20	23	2.5	7	21	24	2.5	7	21	24	2.6

**SOLAR HEAT CONTROL PROPERTIES
SHEERWEAVE STYLE 2410 PERFORMANCE +**

	High Performance Glass				Low E Glass				6mm Double Clear Glass			
	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K
Glazing Performance	69	39	45	1.1	74	70	80	1.4	79	74	85	2.8
P12 Oyster	3	15	17	0.8	4	29	33	1.0	4	24	27	1.6
P13 Oyster/Beige	4	15	17	0.8	4	29	34	1.0	5	24	26	1.6
P14 Oyster/Pearl Gray	3	15	17	0.8	3	29	33	1.0	4	24	27	1.6
Q20 Beige	4	15	17	0.8	4	30	34	1.0	5	24	28	1.6
Q21 Beige/Pearl Gray	4	14	17	0.8	4	30	35	1.0	5	24	28	1.6
V20 Pearl Gray	3	14	16	0.8	3	28	32	0.9	3	23	26	1.5
V21 Charcoal	3	15	18	0.8	3	30	34	1.0	4	25	28	1.6
V22 Charcoal/Gray	3	15	17	0.8	3	29	34	1.0	4	24	28	1.6
V24 Charcoal/Chestnut	3	15	17	0.8	3	30	34	1.0	4	24	28	1.6
V32 Charcoal/Alpaca	3	15	17	0.8	3	24	27	1.0	4	23	27	1.6
	6mm Single Bronze Glass				6mm Single Clear Glass				3mm Single Clear Glass			
	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K	Light Trans	g-Value/SHGC	SC	U-value in W/m2K
Glazing Performance	49	58	67	5.7	88	84	96	5.7	90	87	100	5.8
P12 Oyster	2	19	22	2.4	4	21	23	2.4	4	20	24	2.4
P13 Oyster/Beige	2	19	22	2.4	5	21	24	2.4	5	21	24	2.4
P14 Oyster/Pearl Gray	2	19	22	2.4	4	20	24	2.4	4	20	23	2.4
Q20 Beige	2	19	22	2.5	5	21	24	2.5	5	21	24	2.5
Q21 Beige/Pearl Gray	3	20	23	2.5	5	22	25	2.5	5	22	25	2.5
V20 Pearl Gray	2	18	21	2.4	4	20	23	2.4	4	19	22	2.4
V21 Charcoal	2	19	22	2.4	4	21	25	2.4	4	21	25	2.5
V22 Charcoal/Gray	2	19	22	2.4	4	21	24	2.4	4	21	24	2.4
V24 Charcoal/Chestnut	2	19	22	2.4	4	21	25	2.4	4	21	24	2.4
V32 Charcoal/Alpaca	2	19	22	2.4	4	21	25	2.4	4	21	24	2.4

Mariak Contract
575 W. Manville Street
Rancho Dominguez, CA 90220

Phone: (800) 562-7425
Fax: (800) 459-6999
www.mariak.com

