

Mariak

Many Window Solutions From One Source

SheerWeave Infinity 2 3%

Lead Free, Flame Retardant

Openness Factor:	±3%
UV Blockage:	±97%
Standard Roll Widths:	63", 98"
Composition:	20% TPO Fiber Yarn/80% TPO Coating on TPO yarn
Mesh Weight:	12.82 oz/yd ²
Fabric Thickness (inch):	±0.031
Environmental Certification:	GREENGUARD Certified (Indoor Air Quality) and GREENGUARD for Children and Schools Certified, RoHS Compliant
Fire Classification:	NFPA 701-2004 TM #1 (small scale), NFPA 101 (Class A Rating), ASTM E-84 (Class 1), CAN/ULC-S 109-03 Large
Bacteria & Fungal Resistance:	ASTM E 2180, ASTM G22
Solar Optical Properties:	Fenestration data is available upon request.
Railroading:	Yes

SheerWeave Infinity 2 5%

Lead Free, Flame Retardant

Openness Factor:	±5%
UV Blockage:	±95%
Standard Roll Widths:	63", 98"
Composition:	20% TPO Fiber Yarn/80% TPO Coating on TPO yarn
Mesh Weight:	13.69oz/yd ²
Fabric Thickness (inch):	±0.030
Environmental Certification:	GREENGUARD Certified (Indoor Air Quality) and GREENGUARD for Children and Schools Certified, RoHS Compliant
Fire Classification:	NFPA 701-2004 TM #1 (small scale), NFPA 101 (Class A Rating), ASTM E-84 (Class 1), CAN/ULC-S 109-03 Large
Bacteria & Fungal Resistance:	ASTM E 2180, ASTM G22
Solar Optical Properties:	Fenestration data is available upon request.
Railroading:	Yes